



EasyGate SG

## EasyGate SG / SR 1000 & 1320

### Type

Swing technology  
 1 000 (length of cabinet in mm)  
 1 320 (length of cabinet in mm)  
 1 wing / 2 wings  
 SG model - round front  
 SR model - square front

### Safety & Security Detection

- 24 pairs of IR sensors - version 1 000
- 36 pairs of IR sensors - version 1 320
- Safety & Security levels
- Tailgating / Cross over detection

### Dimensions

Cabinet height	990 mm	38.98"
Cabinet length	1 000 mm	39.37"
	1 320 mm	51.97"
Cabinet width	120 mm	4.72"
Barrier height	850 mm	33.46"
Passage width standard*	650 mm	25.59"
Passage width max.*	920 mm	36.22"

1 000 mm (1 320 mm cabinet length)



EasyGate SG 1000



EasyGate SR 1000

\* For 2 wings type



EasyGate SR

**Material and Colours**

Cabinet	brushed stainless steel
Top Lid	black glass
Barriers	tempered glass barrier panels (10 mm / 0.39")
Side infill panel	tempered glass panels (6 mm / 0.24")

**Operating Environment**

Indoor

**Drive Mechanism**

Fail-Safe

MCBF 5 000 000

**Emergency Mode**

Open automatically in the exit direction

**Optional Accessories**

- RFID reader bracket (flush mounted)
- Access light / Lane light / Wing light
- WAV player
- Pressure sensing top
- Hinge capping
- Ethernet interface
- RF remote control
- EasyTouch / TouchPanel / T-MON SW
- SuperCap (emergency power back-up)
- Alternative surface finishes / Optional top finishes
- Integration of BarCode scanner
- Ramp LT
- Outdoor package

